

Medium Wheel Loader LGL40F

	wheel Loader LGL40F
Engine	
Model	6135K-13b
Туре	Direct injection,water cooled
Rated power	128KW
Rated speed	2000rpm
Rated fuel consumption	238g/Kw.h
Main Technical Specification	
Rated load	4000Kg
Operating weight	13800Kg
Rated bucket capacity	2.3m3
Max. breakout force	134kN
Max. dump clearance	2815mm
Dump reach	1050mm
Dump angle at any position	45°
Digging depth (with bucket bottom horizontal)	190mm
Min. turning radius	
Outside of bucket	6300mm
Outside of rear wheel	5730mm
Oscillating angle of rear axle	±11°
Lifting time of bucket	≤6.2s
Lowering time of bucket	≤3.8s
Dumping time	≤1.8s
Working Equipment	
Model of oil pump	CBGj3140
System pressure	17.7Mpa
Model of multi-way directional valve	D32II
Pilot valve	DJS2-UX/UU
Axle And Tyre	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China Post Code: 201100 E-mail: info@shlongji.com

Tel: +86-21-541-71571 Fax: +86-21-541-71572

Type of main reducer	Spiral bevel gear, single stage	
Gear ratio of main reducer	5.286	
Type of final reducer	Single stage planetary	
Gear ratio of final reducer	4.4	
total ratio	23.258	
Max. tractive force	123kN	
Tyre size	20.5-25	
Transmission System		
Torque Converter		
Туре	4-elements. double stage(China advance)	
Torque ratio	4	
Cooling type	Pressure oil circulating	
Gear box		
Туре	Power shift(China advance)	
Gear shifts (Forward/Reverse)	F2/R1	
Traveling speed(Km/h)		
Forward/Reverse I	11/15	
Forward II	36	
Braking System		
Service brake	Air over oil activate 4 wheel brake with capliar disc brake	
Air pressure	0.68Mpa	
Parking brake	Drum brake; manual control cutting-off air brake	
Steering System		
Туре	central articulated frame. Co-axis flow amp. Steering	
Model of steering pump	CBGj2063/1016-XF	
System pressure	14MPa	
Articulated steering angle	38±1°(L/R)	
Dimensions		
Length(with bucket on ground)	7170mm	
Width(to outside of wheels)	2570mm	
Height(To the top of the cab)	3360mm	
Bucket width	2697mm	
Wheel base	3080mm	
Tread	2050mm	
Ground clearance	400mm	
Service Capacities		
Fuel tank	200L	
Engine crank case	13.5L	
Converter and gear box	45L	

Tel: +86-21-541-71571 Fax: +86-21-541-71572