

LGR210 single drum vibratory roller (mechanical transmission)

LGR210 single drum vibratory roller is equipped with YC6108G engine, PERMCO/HERCULES vibrating pump and motor, mechanical drive transmission, which is suitable for non-cohesive materials, such as sandy soil, gravel, crushed stones, rock fillings and slightly cohesive soils, designed for large foundation constructions such as high-class highways, mines, dams, airports, harbors, railways and industrial areas.

| Engine | |
|-------------------------------|--|
| Model | YC6108G |
| Туре | Vertical, water cooled, direct injection |
| Rated power | 85KW |
| Rated speed | 2000rpm |
| Rated fuel consumption | 215g/kw∙h |
| Main Technical Specification | |
| Operating weight | 10000kg |
| Туре | Hydraulic vibration |
| Frequency | 30Hz |
| Amplitude | 0.9/1.8 mm |
| Static linear load | 230N/cm |
| Vertical oscillation | 10° |
| Drum shell thickness | 24mm |
| Centrifugal force(high ampl.) | 240KN |
| Centrifugal force(low ampl.) | 130KN |
| Transmission System | |
| Туре | Mechanical drive(gear box) |
| Grade ability | 35% |
| Gear shifts(Forward/Reverse) | F3/R3 |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

| Traveling speed(km/h) | |
|-----------------------|--|
| Forward/Reverse I | 1.8/1.8 |
| Forward/Reverse II | 3.7/3.7 |
| Forward/ReverseIII | 9.7/9.7 |
| Axle | <u> </u> |
| Drive type | Rear wheel drive |
| Front axle load | 6000kg |
| Rear axle load | 4000kg |
| Steering System | <u> </u> |
| Туре | Articulated frame, hydraulic steering |
| Steering cylinder | Two cylinders |
| Steering pump | Gear pump |
| Working pressure | 12MPa |
| Steering angle | ±36° |
| Min. steering radius | 6500mm (outer side),4870mm (inner side) |
| Braking System | • |
| Service brake | Disc brake, actuate rear wheels |
| Parking brake | Hand operated drum brake |
| Dimensions | |
| Overall length | 5640mm |
| Overall width | 2258mm |
| Overall height | 2970mm |
| Drum width | 2100mm |
| Wheel base | 3080mm |
| Drum Dia. | 1400mm |
| Tyre size | 17.5-25 |
| Ground clearance | 360mm |
| Service Capacities | • |
| Hydrauclic tank | 150L |
| Gear box | 25L |
| Drive alxe | 25L |
| Brake booster | 10L |
| Fuel tank | 180L |
| Engine crank case | 16L |

Tel: +86-21-541-71571 Fax: +86-21-541-71572